



MTU 20V 4000 G63 (FO)	CGT Stamford LVSI 804	Generator Model:	G3050SMU5
--------------------------	--------------------------	---------------------	------------------

50 Hz	3-Phase	Power Factor Cos Φ = 0.8	Emissions Non-Certified
-------	---------	----------------------------------	----------------------------

RATINGS	PRIME POWER (PRP)		STANDBY POWER (ESP)		
	G3050S-MU5				
Voltage	kVA	kWe	kVA	kWe	Amps
415/240	2800	2240	3050	2440	4243
400/230	2800	2240	3050	2440	4402
380/220	2800	2240	3050	2440	4634

Definition of Ratings & Reference Conditions
<p>Prime Power (PRP) is the nominal output continuously available, where the average load (variable) does not exceed 75% of the prime power rating. 10% overload is available for a maximum of 1 hour in 12 hours of operation.</p> <p>Standby Power (ESP) is the maximum output available, for up to 500 hours per year, where the average load does not exceed 85% of the standby power rating. No overload is available.</p> <p>Standard Reference Conditions: air inlet temperature 25°C (77°F), barometric pressure 100kPa, [100m (328ft) altitude], 30% relative humidity.</p> <p>Note: The above ratings may be subject to derate at different operating conditions. Please see the Derate Guidelines on the Broadcrown website.</p> <p>All power ratings and reference conditions in accordance with ISO 8528-1 and ISO 3046-1.</p>

	<p>Key Features:</p> <ul style="list-style-type: none"> • Efficient water cooled diesel engine. • Single bearing CGT Stamford alternator • Radiator with pressure cap and drain point • Fully guarded engine-driven fan • Fully welded steel baseframe with lifting / jacking points • Various fuel system options • Heavy duty rubber anti-vibration mountings • 24V starter batteries and connecting cables • Separate engine-driven battery charging alternator • Spin on oil and fuel filters and dry type air filter element • Auto Start control system with digital instrumentation • Factory Test Certificate • Operation & Maintenance Manual • Wide range of optional extra features available
---	---



Overall Dimensions & Weights - Open Set
Length (L) = 7039mm
Width (W) = 2394mm
Height (H) = 3192mm
Dry Weight (inc oil) = 20148kg
Operating Weight = 21383kg

	Typical Open Generator Sound Pressure Level at 1m, Free Field (dB)							
Overall dBA	63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA	TBA

All specifications and design are subject to change without notice



G3050SMU5

Jan 2017

ENGINE & COOLING SYSTEM

MTU 20V 4000 G63 (FO)

	SI Units	PRIME	STANDBY	
Performance	Engine Speed	r/min 1500		
	Gross Power	2420	2662	
	Fan Power	54	54	
	Net Power	2366	2608	
	Emissions Certification	—		
	Altitude Capability	m	400	400
General	Cylinders / Type	20 cyl / Vee form / 4-stroke		
	Aspiration / Charge Cooling	Turbocharged / 2 pump 2 loop		
	Governing / Engine Management	"ADEC" Electronic Governor/ECU/CANBus		
	Bore / Stroke	mm	170 / 210	
	Cubic Capacity	litres	95.4	
	BMEP	kPa	2031	2234
Fuel	Fuel Consumption at 100% Power	litres/h	539.0	605.4
	Fuel Consumption at 75% Power	litres/h	410.7	449.4
	Fuel Consumption at 50% Power	litres/h	286.5	312.1
	Total fuel flow	litres/h	1620	
	Standard Fuel Tank Capacity	litres	N/A	
Air	Engine Air Flow	m³/s	2.7	3.0
	Maximum Air Intake Restriction (used filter)	kPa	5	
Exhaust	Exhaust Gas Flow	m³/s	7.1	8
	Exhaust Gas Temperature	°C	530	585
	Maximum Exhaust Back Pressure	kPa	8.5	
	Typical Exhaust Pipe Diameter	mm	450	
Cooling	Radiator Cooling Air Flow	m³/s	38.6	
	Max Restriction to Cooling Air Flow	Pa	200	
	Max Radiator Air-On Temperature	°C	45	
	Maximum Coolant Temperature	°C	104	
	Coolant Capacity - Engine Only	litres	205	
	Total Coolant Capacity	litres	TBA	
Oil	Total Oil Capacity incl Filters	litres	390	
	Typical Oil Pressure at Rated Speed	kPa	450	
	Typical Oil Consumption (>250hrs Operation)	litres/h	1.72	
Thermal	Heat Rejection to Engine Cooling Water	kW	890	980
	Heat Rejection to Charge Cooler	kW	350	430
	Heat Radiated From Engine (Typical)	kW	105	105
Elec	Electrical System Voltage	V	24	
	Battery Type		TBA	
	Battery Capacity SAE CCA	A	TBA	

ALTERNATOR

CGT STAMFORD LVSI 804 S2

	SI Units	PRIME	STANDBY	
General Data	Manufacturer	Cummins Generator Technologies - STAMFORD		
	Model (may vary with voltage)	LVSI 804 S2	LVSI 804 S2	
	Operating Temperature	°C	40	27
	Coupling / No. of Bearings	Direct / Single Bearing		
	Phase / Poles / Winding Type	3-Phase / 4-Pole / Winding 311		
	Power Factor	Cos Φ = 0.8		
	Excitation	Separately excited by PMG		
	Insulation System	Class H		
	AVR Type	MA330		
	Voltage Regulation	± 0.5%		

All specifications and design are subject to change without notice



G3050SMU5

Jan 2017

STANDARD CONTROL SYSTEM BC 7310 Digital Auto Start

The standard control system for this model is **BC 7310** (photo), based on the Deep Sea Electronics DSE7310 Digital Auto Start controller.

This provides for the manual and automatic remote start of the generator, together with full control and protection of the engine via the ECU. LCD digital display of :

- Coolant temperature with high temperature alarm and shutdown
- Oil pressure with low pressure alarm and shutdown
- Oil temperature, engine operating hours, battery charge volts and amps
- Volts, with Under/Over Volts protection
- Amps, with Over Current protection
- Frequency, kW, kVA, Power Factor

Also featuring :

- Full RS485 Telemetry implementation
- Automatic cool-down timer function
- Emergency Stop button
- Ample auxiliary inputs/outputs for optional features
- Optional (shown) - battery charger and door mounted illuminated switch.



CONTROL SYSTEM OPTIONS

The **BC 7320** control system (just the DSE7320 module is shown here) has an identical feature set to the BC 7310 but with the addition of full AMF functionality with integrated mains monitoring.



Finally, **BC 8610 & BC 8620** control systems provide the same features as BC 7310 & BC 7320 respectively, plus :

- BC 8610 - Set-to-Set Synchronisation
- BC 8620 - Single Set-to-Mains Supply Synchronisation with integrated mains monitoring

For Multi Set-to-Mains synchronisation, each set requires BC 8610 with the addition of one mains monitoring panel **BC 8660** (not illustrated). See the Synchronisation Guidelines for further details.

All designs and specifications subject to change without notice